

BLADE FENCE

1800 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 40 x 40 x 1.8 mm SHS Rails
- 65 x 16 x 1.2 mm RHS Pickets

Material & Welds

- 6063 T6 Aluminium
- 2x 15mm Welds at Each Joint

Coating Systems

- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 10 year Warranty Powder

Warranty

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure

Colours



Black



Monument



Surfmist


**Custom powder coat colours available on special order.*

Picket Spacing

- 85mm Centres | 69mm Airspace


Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005




PICKET CAP DETAILS

65 x 16 mm Press Fit Aluminium Cap



PICKET SPACING

85mm Centres | 69mm Airspace



JOINT DETAILS

Each Picket Face Welded to Rails with 2x 15mm Welds

BLADE FENCE

1800 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 40 x 40 x 1.8 mm SHS Rails
- 65 x 16 x 1.2 mm RHS Pickets

Material & Welds

- 6063 T6 Aluminium
- 2x 15mm Welds at Each Joint

Picket Spacing

- 85mm Centres | 69mm Airspace

Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005

Fence Brackets

- 40 x 40 Fence Brackets (Colour Matched) - 2 Hole Double Lugged, 4 Hole Double Lugged, (4 Brackets per Panel)
- 40 x 40 Adjustable Brackets (Colour Matched) - 2 Hole Single Lugged, Horizontal/Vertical Adjustable (4 Brackets per Panel)
- Colour Matched Self Tapping Screws - 12-14 x 20mm

Post Options


- SHS 100 x 2 mm Anti-twist Inground Posts with Press Fit Caps
- SHS 100 x 2 mm Base-plated Posts with Press Fit Caps

Coating Systems


- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 15 year Warranty Powder

Warranties

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure




*FENCE LAYOUT IS ILLUSTRATED FROM THE NON-SECURE SIDE.




INGROUND POST ANTI-TWIST FEATURE

Inground post stamped at bottom, forming a widened section to prevent twisting



BASE PLATE DETAILS

200 X 200 base plate with Ø18mm holes in 150 x 150 hole pattern



FIXING DETAILS

4x FB4040-2H Brackets per panel, 2x TEK121420 Screws per bracket