

FLAT TOP

1500 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 38 x 25 x 1.6 mm RHS Rails
- 19 x 1.2 mm CHS Pickets

Material & Welds

- Galvanised Steel
- 2x 8mm Welds at Each Joint

Picket Spacing

- 103mm Centres | 84mm Airspace

Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005

Coating Systems

- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 10 year Warranty Powder

Warranty

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure

Colours



Black




Monument




Surfmist

**Custom powder coat colours available on special order.*




PICKET TOP DETAILS

Single Punched Top Rail with Picket Welded on Bottom Side of the Rail



PICKET SPACING

103mm Centres | 84mm Airspace



JOINT DETAILS

Each Picket Welded to Rails with 2x 8mm Welds

FLAT TOP

1500 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 38 x 25 x 1.6 mm RHS Rails
- 19 x 1.2 mm CHS Pickets

Material & Welds

- Galvanised Steel
- 2x 8mm Welds at Each Joint

Picket Spacing

- 103mm Centres | 84mm Airspace

Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005

Fence Brackets

- 38 x 25 Fence Brackets (Colour Matched) - 2 Hole Double Lugged (4 Brackets per Panel)
- 38 x 25 Adjustable Brackets (Colour Matched) - 2 Hole Single Lugged, Horizontal/Vertical Adjustable (4 Brackets per Panel)
- Colour Matched Self Tapping Screws - 12-14 x 20mm

Post Options


- SHS 65 x 1.6 mm / SHS 75 x 2 mm Anti-twist Inground Posts with Press Fit Caps
- SHS 65 x 1.6 mm / SHS 75 x 2 mm Base-plated Posts with Press Fit Caps

Coating Systems


- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 15 year Warranty Powder

Warranties

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure




*FENCE LAYOUT IS ILLUSTRATED FROM THE NON-SECURE SIDE.



INGROUND POST ANTI-TWIST FEATURE

Inground post stamped at bottom, forming a widened section to prevent twisting



BASE PLATE DETAILS

150 X 150 base plate with Ø14mm holes in 110 x 110 hole pattern



FIXING DETAILS

4x FB3825-2H Brackets per panel, 2x TEK121420 Screws per bracket