

ROBUST BLADE

1800 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 38 x 25 x 1.8 mm RHS Rails
- 65 x 16 x 1.2 mm RHS Pickets

Material & Welds

- 6063 T6 Aluminium
- 2x 15mm Welds at Each Joint

Coating Systems

- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 10 year Warranty Powder

Warranty

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure

Colours



Black



Monument



Surfmist


**Custom powder coat colours available on special order.*

Picket Spacing

- 85mm Centres | 69mm Airspace


Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005




PICKET CAP DETAILS

65 x 16 mm Press Fit Aluminium Cap



PICKET SPACING

85mm Centres | 69mm Airspace



JOINT DETAILS

Each Picket Face Welded to Rails with 2x 15mm Welds

ROBUST BLADE

1800 x 2300 Fence Panel

IDEAL FOR RESIDENTIAL FENCING,
BRICK PIER INFILLS & MORE!

Panel Specs

- 38 x 25 x 1.8 mm RHS Rails
- 65 x 16 x 1.2 mm RHS Pickets

Material & Welds

- 6063 T6 Aluminium
- 2x 15mm Welds at Each Joint

Picket Spacing

- 85mm Centres | 69mm Airspace

Standards

- Australian Pool Safety Standard AS1926.1 (2012)
- Powder Coating Standard AS4506-2005

Fence Brackets

- 38 x 25 Fence Brackets (Colour Matched) - Single Lugged, (4 Brackets per Panel)
- 25 x 38 Adjustable Brackets (Colour Matched) - Double Lugged, Horizontal/Vertical Adjustable (4 Brackets per)
- Colour Matched Self Tapping Screws - 12-14 x 20mm

Post Options



- SHS 75 x 2 mm / SHS 100 x 2 mm Anti-twist Inground Posts with Press Fit Caps
- SHS 75 x 2 mm / SHS 100 x 2 mm Base-plated Posts with Press Fit Caps

Coating Systems

- Bonderite M-NT: Nano Ceramic Coating
- Interpon or PPG 15 year Warranty Powder


Warranties

- 10-year warranty on powder coating with cleaning procedure
- 25-year lifetime recommendation with cleaning procedure



INGROUND POST ANTI-TWIST FEATURE

Inground post stamped at bottom, forming a widened section to prevent twisting



BASE PLATE DETAILS

150 X 150 base plate with Ø14mm holes in 110 x 110 hole pattern



FIXING DETAILS

4x FB3825-2H Brackets per panel, 2x TEK121420 Screws per bracket